

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name <u>MC-Fastpack EP solid - Komponente B</u>

· Article number: 2901

1.2 Relevant identified uses of the substance or mixture

and uses advised against No further relevant information available.

· Application of the substance

/ the mixture Epoxy coating Epoxy impregnation

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

Informing department: Technische Abteilung

msds@mc-bauchemie.de

· 1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +48612864565

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage. Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to

Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

Hazard pictograms



(Contd. on page 2)



Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

(Contd. of page 1)

· Signal word

Danger

· Hazard-determining

components of labelling:

1,3-Cyclohexanedimethanamine

Polyamine-Addukt

2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid

Formaldehyde, polymers with diethylenetriamine and styrenated

phenol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(*methylamine*)

· Hazard statements H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

• **Precautionary statements** P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all

contaminated clothing. Rinse skin with water/

shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it

before reuse.

· 2.3 Other hazards

Results of PBT and vPvB assessment
PBT:
Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• **Description:** Binding agent with colouring agents.

Mixture consisting of the following components.

| | · Dangerous components: | | |
|---|------------------------------------------------|------------------------------------------------------------------------------------|----------|
| Ī | CAS: 2579-20-6 | 1,3-Cyclohexanedimethanamine | ≥5-<25% |
| | EINECS: 219-941-5 | Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317 | |
| | CAS: 61788-44-1 | 2,4,6-Tris-(1-Phenyl-Ethyl) carbolic acid | ≥10-<25% |
| | EINECS: 262-975-0 | Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317 | |
| Ī | | Polyamine-Addukt | ≥3-<10% |
| | | Eye Dam. 1, H318; Skin Irrit. 2, H315 | |
| | CAS: 100-51-6 | Benzyl alcohol | <10% |
| | EINECS: 202-859-9 Reg.nr.: 01-2119492630-38 | Acute Tox. 4, H302; Acute Tox. 4, H332 | |
| - | | | |

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

| | (Co | ontd. of page 2 |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-----------------|
| CAS: 7727-43-7 | barium sulphate, natural | <10% |
| EINECS: 231-784-4 | substance with a Community workplace exposure limit | |
| CAS: 69-72-7 | Salicylic acid | ≥1-<2.5% |
| EINECS: 200-712-3 | Eye Dam. 1, H318; Acute Tox. 4, H302 | |
| CAS: 1293368-66-7 | Formaldehyde, polymers with diethylenetriamine and styrenated phenol | ≥1-<2.5% |
| | Skin Corr. 1B, H314; Eye Dam. 1, H318; Skin Sens. 1, H317 | |
| CAS: 2855-13-2 | 3-aminomethyl-3,5,5-trimethylcyclohexylamine | ≥0.1-<1% |
| EINECS: 220-666-8 Reg.nr.: 01-2119514687-32 | Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | |
| CAS: 1477-55-0 | m-phenylenebis(methylamine) | ≥0.1-<1% |
| EINECS: 216-032-5 Reg.nr.: 01-2119480150-50 | Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Sens. 1, H317; Aquatic Chronic 3, H412 | |
| · Additional information | For the wording of the listed hazard phrases refer to se | ction 16 |

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

After inhalation
 After skin contact
 After eye contact
 Supply fresh air and call for doctor for safety reasons.
 Instantly wash with water and soap and rinse thoroughly.
 Rinse opened eye for several minutes under running water.

Seek medical treatment.

· After swallowing Rinse out mouth and then drink plenty of water.

Instantly call for doctor.

· 4.2 Most important symptoms and effects, both acute and

delayed No further relevant information available.

· **Danger** Danger of gastric perforation.

· 4.3 Indication of any

immediate medical attention

and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

• Suitable extinguishing agents CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

· For safety reasons unsuitable

extinguishing agents

Water with a full water jet.

5.2 Special hazards arising from the substance or

mixture Can be released in case of fire

Carbon monoxide (CO) Nitrogen oxides (NOx)

(Traces)

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

(Contd. of page 3)

· 5.3 Advice for firefighters

• **Protective equipment:** Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

6.2 Environmental

precautions:

Wear protective equipment. Keep unprotected persons away.

Do not allow to enter drainage system, surface or ground water.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust).

Dispose of contaminated material as waste according to item 13.

· 6.4 Reference to other

sections

See Section 8 for information on personal protection equipment.

See Section 7 for information on safe handling

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling Store in cool, dry place in tightly closed containers.

Open and handle container with care.

· Information about protection

against explosions and fires: No special measures required.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage

· Requirements to be met by

storerooms and containers: No special requirements.

· Information about storage in

one common storage facility: Store away from foodstuffs.

· Further information about

storage conditions: Protect from heat and direct sunlight.

Keep container tightly sealed.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see item 7.

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

(Contd. of page 4)

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

7727-43-7 barium sulphate, natural

WEL Long-term value: 10* 4** mg/m³
*inhalable dust **respirable dust

• Additional information: The lists that were valid during the compilation were used as basis.

· 8.2 Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Keep away from foodstuffs, beverages and food.

Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

Avoid contact with the eyes and skin.

· Protection of hands: Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

The selection of the suitable gloves does not only depend on the

material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

The exact break trough time has to be found out by the

manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

Tightly sealed safety glasses.

Body protection: Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: Black
Smell: Amine-like

· pH-value at 20 °C: >8

· Change in condition

Melting point/freezing point: Not determined

Initial boiling point and boiling range: 205 °C

· Flash point: 101 °C

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

| | (Contd. of page |
|-------------------------------------------------------------------------|------------------------------------------------------------------------------------------|
| · Ignition temperature: | 380 °C |
| · Self-inflammability: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation o explosive air/steam mixtures is possible. |
| · Steam pressure at 20 °C: | 0.1 hPa |
| · Density at 20 °C | 1.5 g/cm³ |
| · Solubility in / Miscibility with Water: · 9.2 Other information | Partly miscible No further relevant information available. |

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values that are relevant for classification:

2579-20-6 1,3-Cyclohexanedimethanamine

Oral LD50 700 mg/kg (Ratte)
Dermal LD50 1,700 mg/kg (Ratte)

Primary irritant effect:

· Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin

sensitisation May cause an allergic skin reaction.

• CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity
 Carcinogenicity
 Reproductive toxicity
 STOT-single exposure
 STOT-repeated exposure
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.
 Based on available data, the classification criteria are not met.

(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

(Contd. of page 6)

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

2579-20-6 1,3-Cyclohexanedimethanamine

EC50/24h 90 mg/l (Pseudokirchneriella subcapitata)

LC50/48h | 130 mg/l (Leucidus idus)

12.2 Persistence and

degradability No further relevant information available.

· 12.3 Bioaccumulative

potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

· General notes: Do not allow product to reach ground water, water bodies or

sewage system.

Danger to drinking water if even small quantities leak into soil.

12.5 Results of PBT and vPvB assessment
 PBT: Not applicable.
 vPvB: Not applicable.

• 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

• Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· European waste catalogue

08 00 00 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU)
OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES,
SEALANTS AND PRINTING INKS

08 01 00 wastes from MFSU and removal of paint and varnish

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

· Uncleaned packagings:

Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN2735

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

| 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (1, Cyclohexanedimethanamine) AMINES, LIQUID, CORROSIVE, N.O.S. (1, Cyclohexanedimethanamine) |
|--------------------------------------------------------------------------------------------------------------------------------------|
| |
| 8 (C7) Corrosive substances. 8 |
| 8 Corrosive substances. 8 |
| III |
| No |
| Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" acids. |
| t II Not applicable. |
| |
| 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml |
| 3 <i>E</i> |
| 5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 100 ml |
| |

(Contd. on page 9)



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 06.11.2018 Printing date 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

(Contd. of page 8)

UN "Model Regulation":

UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (1,3-CYCLOHEXANEDIMETHANAMINE), 8, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· REGULATION (EC) No

1907/2006 ANNEX XVII

Conditions of restriction: 3

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H302 Harmful if swallowed. · Relevant phrases

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 06.11.2018 Revision: 06.11.2018

Trade name MC-Fastpack EP solid - Komponente B

(Contd. of page 9)

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic

hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· * Data compared to the previous version altered.