

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2019 Revision: 19.01.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

• Trade name MC-Injekt 3000 HPS - Komponente B 2

• CAS Number: 7775-27-1 • EC number: 231-892-1

 1.2 Relevant identified uses of the substance or mixture and uses advised against

nd uses advised against No further relevant information available.

· Application of the substance

/ the mixture Construction chemicals

Injektion

Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: MC-Bauchemie Müller GmbH & Co. KG

Am Kruppwald 1-8 D-46238 Bottrop Tel.: +49(0)2041-101-0 Fax.: +49(0)2041-101-400 E-Mail: info@mc-bauchemie.de

MC-Bauchemie AG Hagackerstr. 10 CH-8953 Dietikon Tel.: +44-7400510 Fax: +44-7400533

· Informing department: Technische Abteilung msds@mc-bauchemie.de

· 1.4 Emergency telephone

number: Tel.: +49 / (0)700 24112112 (MCR)

Tel.: +48612864565

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Ox. Sol. 2 H272 May intensify fire; oxidiser.
Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

· Labelling according to

Regulation (EC) No 1272/2008 The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)



Page 2/10

(Contd. of page 1)

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 19.01.2019 Printing date 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

· Hazard pictograms





GHS07

· Signal word Danger

· Hazard-determining

components of labelling:

· Hazard statements

disodium peroxodisulphate H272 May intensify fire; oxidiser. H302 Harmful if swallowed. H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

· Precautionary statements

Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking. P220 Keep/Store away from clothing/combustible materials. P221 Take any precaution to avoid mixing with

combustibles.

P285 In case of inadequate ventilation wear respiratory

protection.

P403+P233 Store in a well-ventilated place. Keep container tightly

closed.

P405 Store locked up.

· 2.3 Other hazards

· Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

P210

· 3.1 Chemical characterisation: Substances

CAS No. Designation: 7775-27-1 disodium peroxodisulphate

· Identification number(s):

· EC number: 231-892-1

SECTION 4: First aid measures

· 4.1 Description of first aid measures

General information Symptoms of poisoning may even occur after several hours;

therefore medical observation for at least 48 hours after the

Instantly remove any clothing soiled by the product. Do not leave affected persons unsupervised.

Take affected persons out of danger area and instruct to lie down.

Personal protection for the First Aider.

(Contd. on page 3)



Page 3/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2019 Revision: 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 2)

• After inhalation Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position

for transport.

Do not use mouth to mouth or mouth to nose resuscitation. Instantly wash with water and soap and rinse thoroughly.

· After eye contact Rinse opened eye for several minutes under running water. Then

consult a doctor.

· After swallowing Do not induce vomiting; instantly call for medical help.

Rinse out mouth and then drink plenty of water.

· 4.2 Most important symptoms and effects, both acute and

delayed Allergic reactions

· 4.3 Indication of any

· After skin contact

immediate medical attention

and special treatment needed Medical supervision for at least 48 hours

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents Water haze

Water spray jet

· For safety reasons unsuitable

extinguishing agents

5.2 Special hazards arising

from the substance or

mixture

Water with a full water jet.

Can be released in case of fire

Sulphur dioxide (SO2)

· 5.3 Advice for firefighters

Protective equipment: Wear self-contained breathing apparatus.
 Additional information Cool endangered containers with water spray jet.

Dispose of fire debris and contaminated fire fighting water in

accordance with official regulations.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and

emergency procedures Ensure adequate ventilation

Avoid causing dust.

Use breathing protection against the effects of fumes/dust/aerosol.

Keep away from ignition sources

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental

precautions: Damp down dust with water spray jet.

Do not allow to enter drainage system, surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Collect mechanically.

(Contd. on page 4)



Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 19.01.2019 Printing date 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 3)

Dispose of the material collected according to regulations.

Ensure adequate ventilation.

· 6.4 Reference to other

sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling

Any deposit of dust which cannot be avoided must be removed

regularly.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of dust.

· Information about protection

against explosions and fires: Substance/product is oxidising when dry.

Substance/product can reduce the ignition temperature of

flammable substances.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

Storage

· Requirements to be met by

storerooms and containers:

Store only in the original container.

Information about storage in

one common storage facility: Do not store together with reducing agents, heavy-metal

compounds, acids and alkalis.

Store away from flammable substances.

· Further information about

storage conditions:

Store in cool, dry conditions in well sealed containers.

Protect from humidity and keep away from water.

This product is hygroscopic.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· Additional information about

design of technical systems: No further data; see item 7.

· 8.1 Control parameters Allgemeiner Staubgrenzwert:

> Einatembare Fraktion (E-Staub): 10 mg/m³ (Schichtmittelwert) Alveolengängige Fraktion (A-Staub): 3 mg/m³ (Schichtmittelwert)

· Components with critical

values that require

monitoring at the workplace: Not required.

· Additional information: The lists that were valid during the compilation were used as basis.

(Contd. on page 5)



Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2019 Revision: 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 4)

· 8.2 Exposure controls

· Personal protective equipment

· General protective and

hygienic measures Do not inhale dust / smoke / mist.

Keep away from foodstuffs, beverages and food. Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.

• Protection of hands: Protective gloves.

Selection of the glove material on consideration of the penetration

times, rates of diffusion and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

· Material of gloves Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the

application.

· Penetration time of glove

material

Penetration: ≥ 480 min

The exact break trough time has to be found out by the

manufacturer of the protective gloves and has to be observed.

• Eye protection: Safety glasses

Tightly sealed safety glasses.

· Body protection: Impervious protective clothing

Protective work clothing.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Powder
Colour: White

Smell: Odourless
Odour threshold: Not determined.

• pH-value (250 g/l) at 25 °C: 4.3

· Change in condition

Melting point/freezing point: ontleding 200 °C Not applicable

Initial boiling point and boiling range: Not applicable

· Flash point: Not applicable

· Inflammability (solid, gaseous) Contact with combustible material may cause fire.

(Contd. on page 6)



Page 6/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2019 Revision: 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

	(Contd. of page	
· Decomposition temperature:	~180 °C °C (SADT (UN-Test H.4))	
· Self-inflammability:	Not determined.	
Explosive properties:	Explosive when mixed with combustible material.	
· Critical values for explosion:		
Lower:	Not determined.	
Upper:	Not determined.	
· Steam pressure:	Not applicable.	
· Density at 20 °C	1.20 ~ 2.59 g/cm³	
· Settled apparent density at 20 °C	1150 ~ 1350 kg/m³	
Relative density	Not determined.	
· Vapour density	Not applicable.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
Water at 20 °C:	545 ~ 556 g/l	
· Partition coefficient: n-octanol/water:	Not determined.	
· Viscosity:		
dynamic:	Not applicable.	
kinematic:	Not applicable.	
· 9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability Thermal decomposition /

conditions to be avoided: To avoid thermal decomposition do not overheat.

Zündquellen fernhalten

Maßnahmen gegen elektrostatische Aufladungen treffen.

Vor Feuchtigkeit schützen.

In feuchtem Zustand schon bei Raumtemperatur langsame

Zersetzung.

· 10.3 Possibility of hazardous

reactions Reacts with fats and oils

Reacts with alkali (lyes) Danger of bursting

Acts as an oxidizing agent on organic materials such as wood,

paper and fats

Korrosionswirkung auf Gebrauchsmetalle. Feuergefahr bei

Berührung mit brennbaren Stoffen.

Reacts with acids

Reacts with fabric soaked in the product (e.g. cleaning wool)

Reacts with reducing agents

• 10.4 Conditions to avoid No further relevant information available.

(Contd. on page 7)



Page 7/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2019 Revision: 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 6)

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous

decomposition products:

Sulphur oxides (SOx)

Oxygen

Danger of toxic pyrolysis products

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Harmful if swallowed.

· LD/LC50 values that are relevant for classification:

7775-27-1 disodium peroxodisulphate

Oral LD50 920 mg/kg (Ratte)

Dermal LD50 >10,000 mg/kg (Kaninchen)

Inhalative LC50/4 h >5.1 mg/l (Ratte)

· Primary irritant effect:

Causes skin irritation. · Skin corrosion/irritation

· Serious eye damage/irritation Causes serious eye irritation.

· Respiratory or skin

sensitisation May cause allergy or asthma symptoms or breathing difficulties if

inhaled.

May cause an allergic skin reaction.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Based on available data, the classification criteria are not met. · Germ cell mutagenicity · Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure May cause respiratory irritation.

· STOT-repeated exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · Aspiration hazard

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

7775-27-1 disodium peroxodisulphate

LC50/96h 771 mg/l (Oncorhynchus mykiss)

12.2 Persistence and

Anorganic product, is not eliminable from water by means of degradability

biological cleaning processes.

· 12.3 Bioaccumulative

No further relevant information available. potential No further relevant information available. · 12.4 Mobility in soil

· Additional ecological information:

Do not allow undiluted product or large quantities of it to reach · General notes:

ground water, water bodies or sewage system.

(Contd. on page 8)



Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 19.01.2019 Printing date 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 7)

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation Must not be disposed of together with household garbage. Do not

allow product to reach sewage system.

· Waste disposal key number: Die Abfallschlüsselnummer nach der Abfallverzeichnis-Verordnung

(AVV) ist abhängig vom Abfallerzeuger und kann

dadurch für ein Produkt unterschiedlich sein. Die Abfallschlüsselnummer ist daher von jedem Abfallerzeuger

gesondert zu ermitteln.

· Uncleaned packagings:

· Recommendation: Empty contaminated packagings thoroughly. They can be recycled

after thorough and proper cleaning.

14.1 UN-Number		
ADR, IMDG, IATA	UN1505	
14.2 UN proper shipping name		
ADR	<i>1505 SODIUM PERSULPHATE</i>	
IMDG, IATA	SODIUM PERSULPHATE	
14.3 Transport hazard class(es)		
ADR		
Class	5.1 (O2) Oxidising substances.	
Label	5.1	
IMDG, IATA		
Class	5.1 Oxidising substances.	
Label	5.1	
14.4 Packing group		
ADR, IMDG, IATA	III	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Warning: Oxidising substances.	
Kemler Number:	50	
EMS Number:	F-A,S-Q	



Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 19.01.2019 Revision: 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 8)

Stowage Category

Segregation Code SG39 Stow "separated from" ammonium

compounds other than AMMONIUM

PERSULPHATE (UN 1444).

SG49 Stow "separated from" cyanides

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ) 5 kg

Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 1000 g

· Transport category

· Tunnel restriction code Ε

· IMDG

Limited quantities (LQ) 5 kg · Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 g

Maximum net quantity per outer packaging: 1000 g

UN "Model Regulation": UN 1505 SODIUM PERSULPHATE, 5.1, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous

substances - ANNEX I Substance is not listed.

· Seveso category P8 OXIDISING LIQUIDS AND SOLIDS

Qualifying quantity (tonnes)

for the application of lower-

tier requirements

· Qualifying quantity (tonnes) for the application of upper-

tier requirements

50 t

200 t

· National regulations

· Other regulations, limitations

and prohibitive regulations

Die Vorschriften der Chemikalien-Verbotsverordnung sowie

Anhang XVII der Verordnung (EG) Nr. 1907/2006 sind zu

beachten.

(Contd. on page 10)



Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Revision: 19.01.2019 Printing date 19.01.2019

Trade name MC-Injekt 3000 HPS - Komponente B 2

(Contd. of page 9)

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data

specification sheet:

Environment protection department.

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises

dangereuses par chemin de fer (Regulations Concerning the International

Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods

by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Ox. Sol. 2: Oxidizing solids – Category 2 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

· * Data compared to the previous version altered.